



WGS STYLE-797



Braided Packing/PTFE Yarn, Aramid Corners

CONSTRUCTION

WGS Style-797 Multiyarn packing made from pure Aramid fibres corners with Pure PTFE fibres at the running surface.

APPLICATION / SERVICE

WGS Style-797 packing, with its unique combination of PTFE and aramid fibers, is dimensionally stable, non-contaminating, has excellent lubricating and running characteristics, and because of the aramid corners, is very wear resistant. It handles acids, alkalis, and a broad range of chemicals. It is well suited for service in rotary and reciprocating pumps, mixers, agitators and reactors, especially where abrasive wear is a problem.

SE	RV	ICE	LIN	/IITS

Type	Description	Value
Temperature Limits:	Minimum	-100°C
	Maximum	+280°C
Pressure Limits:	Rotating	30 bar
	Reciprocating	100 bar
	Static	180 bar
Shaft Speed:		12 m/s
pH:		2-12

WIN GRAPH SEALS

UNIT NO. 19,RAJ VISHNU IND EST, CHINCHPADA, WALIV VASAI (E), THANE (DIST) PIN- 401 208 MAHARASTRA STATE # 9326470221, 7738618871, 9323961305

Email: wingraphseals@gmail.com: wingraphseals@hotmail.com

Website: www.flexiblegraphite.in